

| | | | |
|---|---------|-------------|-----|
|  | Date | Version No. | 1.0 |
| | Subject | | |

PRODUCT NAME : RF Module

Part NO : SRFU

| ITEM | SRFU | | | | |
|--------------------|---------------------------|------------|------------|------------|------------|
| 중심 주파수 | 260MHz | 1765MHz | 1855MHz | 1970MHz | 2160MHz |
| 밴드폭 | 240~260MHz | Fc ± 15MHz | Fc ± 15MHz | Fc ± 10MHz | Fc ± 10MHz |
| 삽입 손실 | 2.0dB max. | 4.2dB max. | 4.2dB max. | 4.2dB max. | 4.2dB max. |
| 평탄도 | 1.0dBmax. | 0.5dB max. | | | |
| 반사 손실 | 15dB min. | 17dB min. | | | |
| 감쇄도 | -60dB min. | | | | |
| RVS CPL | | 30dB ± 1dB | • | 30dB ± 1dB | • |
| FWD CPL | | • | 30dB ± 1dB | • | 30dB ± 1dB |
| Impedance | 50Ω | | | | |
| Pilot Signal/Level | 1915MHz / -9.5dBm±0.25dBm | | | | |
| Operating Temp | -20℃ ~ +70℃ | | | | |

Graph.





